

Hitachi FXDUO Interactive Whiteboards

Dual inspiration, unlimited potential

Introducing the interactive whiteboard that's so versatile you can use either an electronic pen or finger.



The StarBoard FXDUO line offers classrooms the next generation of interactive whiteboards by allowing up to two inputs for multi-touch control on a durable, electronic-free surface.

Until now your interactive whiteboard came with a choice: electronic pen-driven or stylus/finger-driven.

Now you don't have to choose. The Hitachi FXDUO Line responds to pen or finger. Its low-reflection surface is kind on the eye and it caters for multiple users at once.

Key Benefits:

- Control using multi-touch hand gestures for a natural interface
- No special pens required
- Have two students working on the board
- Electronic-free surface can work with damage

HITACHI
Inspire the Next

FXDUO at a glance:

Robust surface	The surface is robust and the whiteboard works even if there are scratches/dents on the surface
Low reflection	Projector reflection is minimized making it gentle on the eyes
Input Methods	Use a finger/object or an electronic Pen to operate the whiteboard
Simultaneous Inputs	Operate the whiteboard using both hands (gestures). Scroll and Zoom-in/Zoom-out
Field Replaceable Digitizer	A detachable digitizer makes it unnecessary to send the whole unit for repair
Electronic Pen (Optional)	Includes three side buttons



Hardware Specifications FXDUO-77" and FXDUO-63"

Model No.	FXDUO-77	FXDUO-63
Digitizing Methods:	Optical touch: image sensors and infrared	
Input Methods:	Finger, stylus/pen type objects, or FX Duo Electronic Pen*	
Multi-touch	2 points of simultaneous contact for certain software features	
Interface to Computer	USB 1.1, 2.0, or WIFI 802.11g (Requires FXDUO Wireless Kit)*	
Effective Screen Size (inches)	77" (62"(W) X 74" (H))	63" (57"(W) X 45" (H))
Sampling Rate	Approximately 100 points/sec	
Resolution	Approximately 500 lpi	
Accuracy	Approximately ±1.5 mm	
Board/Surface Material	Particle wood (core)/Cured resin (surface)	
Operating Specification	41°-95° Fahrenheit / 5° - 35° Celsius 20% - 80% Humidity without condensation	
Dimensions in	68" (W) X 53" (H) X 3" (D)	57" (W) X 45" (H) X 3" (D)
Dimensions w/ floor stand*	68" (W) X 72" (H) X 24" (D)	57" (W) X 72-86" (H) X 24" (D)
Weight (board)	60 lbs	55 lbs
Weight (w/ floor stand*)	98 lbs	92 lbs
Packaging dimension (board) (floor stand*)	73" (W) 61" (H) X 5" (D)	63" (W) X 52" (H) X 4" (D)
Certificates	FCC, CE, UL, RoHs	
Warranty	Five-year limited equipment warranty upon registration. See hardware manual for details.	

Hitachi Software Engineering America, Ltd.
Interactive Media Solutions Division
Tel: 800.615.9855
Fax: 619.482.5784
Email: starboard@hitachi-soft.com

Hitachi Home Electronics (America), Inc. Business Group
Tel: 800.225.1741
www.hitachi.us/digitalmedia

* Optional accessories

** Specifications subject to change without notice

Distributor information

Specifications are subject to change without notice. Printed 06/08

HITACHI
Inspire the Next